

# Wire Rope Slings

## 2-LEG BRIDLE SLINGS WITH EYE HOIST HOOKS

Wire Rope Diameter	EIPS Capacities in Tons 6x19 & 6x36			Crosby A-342 Master Links	Crosby S-320 Eye Hoist Hooks Alloy (t)	Minimum Length Standard Eyes	Minimum Length Thimble Eyes
	60°	45°	30°				
1/4"	1.1	0.91	0.65	1/2"	1	1' 2"	10"
5/16"	1.7	1.4	1	1/2"	1	1' 6"	1'
3/8"	2.5	2	1.4	1/2"	1.5	1' 8"	1' 2"
7/16"	3.4	2.7	1.9	5/8"	2	2'	1' 4"
1/2"	4.4	3.6	2.5	3/4"	3	2' 3"	1' 6"
9/16"	5.5	4.5	3.2	7/8"	5	2' 8"	1' 8"
5/8"	6.8	5.5	3.9	1"	5	2' 10"	1' 10"
3/4"	9.7	7.9	5.6	1"	7	3' 5"	2' 2"
7/8"	13	11	7.6	1 1/4"	11	3' 11"	2' 5"
1"	17	14	9.8	1 1/2"	11	4' 6"	2' 9"
1 1/8"	21	17	12	1 1/2"	15	5' 2"	3' 2"
1 1/4"	26	21	15	1 1/2"	15	5' 8"	3' 8"
1 3/8"	31	25	18	1 3/4"	22	6'	3' 11"
1 1/2"	37	30	21	1 3/4"	22	7'	4' 2"
1 3/4"	49	40	28	2 1/4"	30	8'	5' 2"
2"	63	52	37	2 1/2"	37	9'	6' 1"
2 1/4"	77	63	44	2 3/4"	45	10'	6' 10"
2 1/2"	94	77	54	2 3/4"	60	11'	7' 5"
2 3/4"	113	92	65	3 1/4"		12'	8' 10"
3"	133	108	77	3 3/4"		13'	9' 6"
3 1/2"	176	144	102	408,000#		16'	11' 2"