

Twin-Path® Slings

Twin-Path Sling Stock No. TPXCF/TPXC	Vertical	Choker	Vertical Basket 90°	Basket Hitches		Approximate Weight (Lbs. per Ft.) (Bearing-Bearing)	Nominal Body Width (In)*
				60°	45°		
1000	10,000	8,000	20,000	17,320	14,140	0.40	1 1/2 – 3
1500	15,000	12,000	30,000	25,980	21,210	0.45	1 1/2 – 3
2000	20,000	16,000	40,000	34,640	28,280	0.51	1 1/2 – 3
2500	25,000	20,000	50,000	43,300	35,350	0.57	2 – 4
3000	30,000	24,000	60,000	51,960	42,420	0.71	2 – 4
4000	40,000	32,000	80,000	69,280	56,560	0.83	2 – 4
5000	50,000	40,000	100,000	86,600	70,700	1.14	2 1/2 – 5
6000	60,000	48,000	120,000	103,920	84,840	1.27	2 1/2 – 5
7000	70,000	56,000	140,000	121,240	98,980	1.38	2 1/2 – 5
8500	85,000	68,000	170,000	147,220	120,190	0.17	3 – 6
10000	100,000	80,000	200,000	173,200	141,400	1.84	3 – 6
12500	125,000	100,000	250,000	216,500	176,750	2.35	4 – 8
15000	150,000	120,000	300,000	259,800	212,100	2.66	4 – 8
17500	175,000	140,000	350,000	303,100	247,450	3.14	4 – 8
20000	200,000	160,000	400,000	346,400	282,800	3.45	5 – 10
25000	250,000	200,000	500,000	433,000	353,500	4.07	5 – 10
27500	275,000	220,000	550,000	476,300	388,850	4.61	6 – 12
30000	300,000	240,000	600,000	519,600	424,200	4.92	6 – 12
40000	400,000	320,000	800,000	692,800	565,600	6.54	7 – 14
50000	500,000	400,000	1,000,000	866,000	707,000	8.15	7 – 14
60000	600,000	480,000	1,200,000	1,039,000	848,000	10.20	11 – 22

*Dimensions can vary according to the hardware or bearing points the slings are used with. Minimum is “tapered” width; maximum is the flat tubing width.